



US006286417B1

(12) **United States Patent**
Bichsel

(10) **Patent No.:** **US 6,286,417 B1**
(45) **Date of Patent:** **Sep. 11, 2001**

(54) **DRUM COOKER**

(76) **Inventor:** **Rudolf Bichsel**, Gyrisbergstrasse 124,
CH-3400 Burgdorf (CH)

(*) **Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

3,135,668	*	6/1964	Wesson	134/132
3,484,360	*	12/1969	Sandrock	366/234
3,760,714	*	9/1973	Lortz	99/404
4,203,358		5/1980	Vogt	
4,335,649		6/1982	Velasco, Jr. et al.	
4,410,553	*	10/1983	McGinty	99/348
4,906,104	*	3/1990	Nishise et al.	366/322
5,329,842	*	7/1994	Zittel	99/348
5,429,041	*	7/1995	Zittel	99/470 X

(21) **Appl. No.:** **09/658,478**

(22) **Filed:** **Sep. 8, 2000**

FOREIGN PATENT DOCUMENTS

06062968 3/1994 (JP).

Related U.S. Application Data

(63) Continuation of application No. PCT/EP99/00796, filed on
Feb. 6, 1999.

(51) **Int. Cl.⁷** **A23L 1/00; A23L 3/00;**
A47J 27/00; A47J 37/12; A23N 12/00

(52) **U.S. Cl.** **99/330; 99/348; 99/352;**
99/355; 99/409; 366/101; 366/220

(58) **Field of Search** **99/325, 330, 348,**
99/352-355, 360, 365, 403-409, 450, 470,
483, 485, 486, 487, 516, 517, 534, 536,
477-479, 443 R, 443 C; 366/81, 91, 101-107,
220-236

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,231,002	*	6/1917	Steere	134/132
1,290,396	*	1/1919	Steere	134/132
1,806,957	*	5/1931	Stocking	134/132
2,166,197	*	7/1939	Schaub	366/322
2,314,871	*	3/1943	DeBack	134/65
2,909,872	*	10/1959	Kearney et al.	134/132

OTHER PUBLICATIONS

XP-002108205—Rotary Cereal Cooker, 1999; 1—page.

* cited by examiner

Primary Examiner—Timothy F. Simone

(74) *Attorney, Agent, or Firm*—Harness, Dickey & Pierce,
P.L.C.

(57)

ABSTRACT

A drum cooker for cooking granular products comprises a vessel mounted to rotate about an axis. At least two nozzle groups are provided opening into said vessel. One of said nozzle groups is arranged in that it opens into a first area of said vessel covered by that granular product. A second nozzle group opens into a second area of said vessel not covered by said granular product. For enhancing the quality of the cooking process, a control means is provided for supplying said gaseous heat-carrying medium at any time to said nozzle group only that opens into that first area covered by said product.

6 Claims, 2 Drawing Sheets

